

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Cook Auto Supply Black Trim Kote

Version number: GHS 1.0

Date of compilation: 2021-10-11

SECTION 1: Identification

1.1 Product identifier

Trade name **Cook Auto Supply Black Trim Kote**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Dye coating

1.3 Details of the supplier of the safety data sheet

Cook Auto Supply
3590 N 126th street
Brookfield WI 53005

262-783-1539

1.4 Emergency telephone number

Emergency information service USA 1.800.535.5053, INTL 1.352.323.3500
24 hour emergency number

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

| Section | Hazard class | Category | Hazard class and category | Hazard statement |
|---------|------------------|----------|---------------------------|------------------|
| A.6 | carcinogenicity | 1A | Carc. 1A | H350 |
| B.6 | flammable liquid | 4 | Flam. Liq. 4 | H227 |

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS08



- Hazard statements

H227 Combustible liquid.
H350 May cause cancer.

- Precautionary statements

P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313 If exposed or concerned: Get medical advice/attention.
P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling C.I. Pigment Black 7

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Cook Auto Supply Black Trim Kote

Version number: GHS 1.0

Date of compilation: 2021-10-11

2.3 Other hazards

This material is combustible, but will not ignite readily.

Hazards not otherwise classified

Very toxic to aquatic life (GHS category 1: aquatic toxicity - acute).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

| Name of substance | Identifier | Wt% | Classification acc. to GHS |
|-------------------------------------|--|----------|----------------------------|
| C.I. Pigment Black 7 | CAS No 1333-86-4 RTECS No FF5800000 | 3 - < 12 | Carc. 1A / H350 |
| dipropylene glycol monomethyl ether | CAS No 34590-94-8 | 1 - < 3 | Flam. Liq. 4 / H227 |

Hazardous ingredients, Consideration of other advice

This table, if present, includes all GHS classified ingredients present above their cut-off limits, even if the finished product is not classified as hazardous by GHS.

Exact percentage of ingredients is withheld as a trade secret.

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Cook Auto Supply Black Trim Kote

Version number: GHS 1.0

Date of compilation: 2021-10-11

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Cook Auto Supply Black Trim Kote

Version number: GHS 1.0

Date of compilation: 2021-10-11

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

Control of the effects

Protect against external exposure, such as
frost

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

| Occupational exposure limit values (Workplace Exposure Limits) | | | | | | | | | | | |
|--|---------------|-----------|------------|-----------|--------------------------|------------|---------------------------|-----------------|--------------------------------|----------|------------------|
| Country | Name of agent | CAS No | Identifier | TWA [ppm] | TWA [mg/m ³] | STEL [ppm] | STEL [mg/m ³] | Ceiling-C [ppm] | Ceiling-C [mg/m ³] | Notation | Source |
| US | kaolin | 1332-58-7 | REL | | 10 (10 h) | | | | | i | NIOSH REL |
| US | kaolin | 1332-58-7 | PEL | | 15 | | | | | i, dust | 29 CFR 1910.1000 |

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Cook Auto Supply Black Trim Kote

Version number: GHS 1.0

Date of compilation: 2021-10-11

| Occupational exposure limit values (Workplace Exposure Limits) | | | | | | | | | | | |
|--|---|------------|------------|------------|--------------------------|------------|---------------------------|-----------------|--------------------------------|----------------------|------------------|
| Country | Name of agent | CAS No | Identifier | TWA [ppm] | TWA [mg/m ³] | STEL [ppm] | STEL [mg/m ³] | Ceiling-C [ppm] | Ceiling-C [mg/m ³] | Notation | Source |
| US | kaolin | 1332-58-7 | REL | | 5 (10 h) | | | | | r | NIOSH REL |
| US | kaolin | 1332-58-7 | PEL | | 5 | | | | | r, dust | 29 CFR 1910.1000 |
| US | kaolin | 1332-58-7 | PEL (CA) | | 2 | | | | | r, noAsbestosSil | Cal/OSHA PEL |
| US | kaolin | 1332-58-7 | TLV® | | 2 | | | | | r, noAsbestosSil | ACGIH® 2019 |
| US | carbon black | 1333-86-4 | PEL (CA) | | 3.5 | | | | | | Cal/OSHA PEL |
| US | carbon black | 1333-86-4 | PEL | | 3.5 | | | | | | 29 CFR 1910.1000 |
| US | carbon black | 1333-86-4 | REL | | 3.5 (10 h) | | | | | appx-A, appx-C | NIOSH REL |
| US | carbon black | 1333-86-4 | TLV® | | 3 | | | | | i | ACGIH® 2019 |
| US | Carbon black in presence of polycyclic aromatic hydrocarbons (PAHs) | 1333-86-4 | REL | | 0.1 (10 h) | | | | | PAHs, appx-A, appx-C | NIOSH REL |
| US | (2-methoxy-methylethoxy)propanol | 34590-94-8 | TLV® | 100 | | 150 | | | | | ACGIH® 2019 |
| US | dipropylene glycol methyl ether | 34590-94-8 | PEL (CA) | 100 | 600 | 150 | 900 | | | | Cal/OSHA PEL |
| US | dipropylene glycol methyl ether | 34590-94-8 | REL | 100 (10 h) | 600 (10 h) | 150 | 900 | | | | NIOSH REL |
| US | dipropylene glycol methyl ether | 34590-94-8 | PEL | 100 | 600 | | | | | | 29 CFR 1910.1000 |

Notation

| | |
|---------------|--|
| appx-A | NIOSH Potential Occupational Carcinogen (Appendix A) |
| appx-C | Appendix C - Supplementary Exposure Limits |
| Ceiling-C | ceiling value is a limit value above which exposure should not occur |
| dust | as dust |
| i | inhalable fraction |
| noAsbestosSil | contains no asbestos and less than 1% free crystalline silica |
| PAHs | as polycyclic aromatic hydrocarbons (PAHs) |
| r | respirable fraction |

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Cook Auto Supply Black Trim Kote

Version number: GHS 1.0

Date of compilation: 2021-10-11

Notation

| | |
|------|--|
| STEL | short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified) |
| TWA | time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified) |

| Relevant DNELs of components of the mixture | | | | | | |
|---|------------|-----------|-----------------------|------------------------------------|-------------------|----------------------------|
| Name of substance | CAS No | End-point | Threshold level | Protection goal, route of exposure | Used in | Exposure time |
| C.I. Pigment Black 7 | 1333-86-4 | DNEL | 2 mg/m ³ | human, inhalatory | worker (industry) | chronic - local effects |
| C.I. Pigment Black 7 | 1333-86-4 | DNEL | 2 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| dipropylene glycol monomethyl ether | 34590-94-8 | DNEL | 950 mg/kg | human, dermal | worker (industry) | chronic - systemic effects |
| dipropylene glycol monomethyl ether | 34590-94-8 | DNEL | 404 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |

| Relevant PNECs of components of the mixture | | | | | | |
|---|------------|-----------|-----------------|-----------------------|------------------------------|------------------------------|
| Name of substance | CAS No | End-point | Threshold level | Organism | Environmental compartment | Exposure time |
| C.I. Pigment Black 7 | 1333-86-4 | PNEC | 5 mg/l | aquatic organisms | freshwater | short-term (single instance) |
| C.I. Pigment Black 7 | 1333-86-4 | PNEC | 5 mg/l | aquatic organisms | marine water | short-term (single instance) |
| dipropylene glycol monomethyl ether | 34590-94-8 | PNEC | 4,168 mg/l | microorganisms | sewage treatment plant (STP) | short-term (single instance) |
| dipropylene glycol monomethyl ether | 34590-94-8 | PNEC | 19 mg/l | aquatic organisms | freshwater | short-term (single instance) |
| dipropylene glycol monomethyl ether | 34590-94-8 | PNEC | 1.9 mg/l | aquatic organisms | marine water | short-term (single instance) |
| dipropylene glycol monomethyl ether | 34590-94-8 | PNEC | 4,168 mg/l | aquatic organisms | sewage treatment plant (STP) | short-term (single instance) |
| dipropylene glycol monomethyl ether | 34590-94-8 | PNEC | 2.2 mg/kg | terrestrial organisms | soil | short-term (single instance) |
| dipropylene glycol monomethyl ether | 34590-94-8 | PNEC | 192 mg/l | aquatic organisms | water | intermittent release |

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Cook Auto Supply Black Trim Kote

Version number: GHS 1.0

Date of compilation: 2021-10-11

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

| | |
|----------------|-----------------------|
| Physical state | liquid |
| Color | black |
| Particle | not relevant (liquid) |
| Odor | characteristic |

Other safety parameters

| | |
|---|-----------------------------|
| pH (value) | not determined |
| Melting point/freezing point | not determined |
| Initial boiling point and boiling range | 100 °C |
| Flash point | 86 °C at 101 kPa closed cup |
| Evaporation rate | Not determined |
| Flammability (solid, gas) | not relevant, (fluid) |

Explosive limits

| | |
|-------------------------------|---|
| - Lower explosion limit (LEL) | 1.1 vol% |
| - Upper explosion limit (UEL) | 3 vol% |
| Vapor pressure | 32 hPa at 25 °C |
| Density | not determined |
| Vapor density | this information is not available |
| Relative density | Information on this property is not available |
| Solubility(ies) | not determined |

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Cook Auto Supply Black Trim Kote

Version number: GHS 1.0

Date of compilation: 2021-10-11

Partition coefficient

| | |
|--|--|
| - n-octanol/water (log KOW) | this information is not available |
| Auto-ignition temperature | 183 °C (auto-ignition temperature (liquids and gases)) |
| Viscosity | not determined |
| Explosive properties | none |
| Oxidizing properties | none |
| Temperature class (USA, acc. to NEC 500) | T3A (maximum permissible surface temperature on the equipment: 180 °C) |

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Cook Auto Supply Black Trim Kote

Version number: GHS 1.0

Date of compilation: 2021-10-11

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

| Name of substance | CAS No | Classification | Number |
|----------------------|-----------|----------------|--------|
| C.I. Pigment Black 7 | 1333-86-4 | 2B | |

Legend

2B Possibly carcinogenic to humans

National Toxicology Program (United States): Report on Carcinogens

| Name of substance | CAS No | Classification | Number |
|----------------------|-----------|-------------------------------|---------------------------|
| C.I. Pigment Black 7 | 1333-86-4 | Known to be human carcinogens | 1st Report on Carcinogens |

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life.

Aquatic toxicity (acute) of components of the mixture

| Name of substance | CAS No | Endpoint | Value | Species | Exposure time |
|-------------------------------------|------------|----------|--------------|-----------------------|---------------|
| C.I. Pigment Black 7 | 1333-86-4 | EC50 | >5,600 mg/l | aquatic invertebrates | 24 h |
| C.I. Pigment Black 7 | 1333-86-4 | ErC50 | >10,000 mg/l | algae | 72 h |
| dipropylene glycol monomethyl ether | 34590-94-8 | LC50 | >150 mg/l | fish | 72 h |
| dipropylene glycol monomethyl ether | 34590-94-8 | ErC50 | >969 mg/l | algae | 72 h |

12.2 Persistence and degradability

Data are not available.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Cook Auto Supply Black Trim Kote

Version number: GHS 1.0

Date of compilation: 2021-10-11

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

DOT UN 3082

IMDG-Code UN 3082

ICAO-TI UN 3082

14.2 UN proper shipping name

DOT Environmentally hazardous substance, liquid, n.o.s.

IMDG-Code ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

ICAO-TI Environmentally hazardous substance, liquid, n.o.s.

14.3 Transport hazard class(es)

DOT 9

IMDG-Code 9

ICAO-TI 9

14.4 Packing group

DOT III

IMDG-Code III

ICAO-TI III

14.5 Environmental hazards

hazardous to the aquatic environment

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Cook Auto Supply Black Trim Kote

Version number: GHS 1.0

Date of compilation: 2021-10-11

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Not regulated under DOT until packaged in single containers larger than 119 gallons each - liquid, or 882 lbs each - solid.

Particulars in the shipper's declaration UN3082, Environmentally hazardous substance, liquid, n.o.s., 9, III
Danger label(s) 9, fish and tree



Environmental hazards YES (hazardous to the aquatic environment)
Special provisions (SP) 8, 146, 173, 335, IB3, T4, TP1, TP29
ERG No 171

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant YES (hazardous to the aquatic environment) (2-ethylhexyl benzoate)
Danger label(s) 9, fish and tree



Special provisions (SP) 274, 335, 969
Excepted quantities (EQ) E1
Limited quantities (LQ) 5 L
EmS F-A, S-F
Stowage category A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Environmental hazards YES (hazardous to the aquatic environment)
Danger label(s) 9, fish and tree



Special provisions (SP) A97, A158, A197
Excepted quantities (EQ) E1
Limited quantities (LQ) 30 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Cook Auto Supply Black Trim Kote

Version number: GHS 1.0

Date of compilation: 2021-10-11

- Specific Toxic Chemical Listings (EPCRA Section 313)

none of the ingredients are listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

| Name of substance | CAS No | Functionality | Authoritative Lists |
|---|------------|----------------------------|----------------------------------|
| water | 7732-18-5 | carrier fluid / dis-solver | |
| Butyl acrylate-methyl methacrylate polymers | 25852-37-3 | polymer | |
| C.I. Pigment Black 7 | 1333-86-4 | colorant | IARC Carcinogens - 2B Prop 65 |
| kaolin | 1332-58-7 | abrasive | |
| 2-ethylhexyl benzoate | 5444-75-7 | co-solvent | |
| nepheline syenite | 37244-96-5 | abrasive | |
| dipropylene glycol monomethyl ether | 34590-94-8 | surfactant | |
| Rhodoline FT-100 | | surfactant | |

- Toxic or Hazardous Substance List (MA-TURA)

none of the ingredients are listed

- Hazardous Substances List (MN-ERTK)

| Name of substance | CAS No | References | Remarks |
|-------------------------------------|------------|---------------|---------|
| C.I. Pigment Black 7 | 1333-86-4 | A, N, O, R, * | |
| dipropylene glycol monomethyl ether | 34590-94-8 | A, O | |

Legend

- * Substances which are regulated by OSHA as carcinogens; have been categorized by the ACGIH as either "human carcinogens" or "suspect of carcinogenic potential for man"; have been evaluated by the International Agency for Research on Cancer (IARC) and found to be carcinogens or potential carcinogens; or have been listed as a carcinogen or potential carcinogen in the Annual Report on Carcinogens published by the National Toxicology Program (NTP).
- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division
- R International Agency for Research on Cancer (IARC) Monographs on the Evaluation of the Carcinogenic Risks to Humans; Overall Evaluations of Carcinogenicity: An Updating of IARC Monographs Volumes 1 to 42, Supplement 7 (1987). Available from: WHO Publications Centre USA

- Hazardous Substance List (NJ-RTK)

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Cook Auto Supply Black Trim Kote

Version number: GHS 1.0

Date of compilation: 2021-10-11

| Name of substance | CAS No | Remarks | Classifications |
|-------------------------------------|------------|---------|-----------------|
| C.I. Pigment Black 7 | 1333-86-4 | | CA |
| dipropylene glycol monomethyl ether | 34590-94-8 | | F2 |

Legend

CA Carcinogenic
F2 Flammable - Second Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

| Name acc. to inventory | CAS No | Classification |
|-------------------------------------|------------|----------------|
| CARBON BLACK | 1333-86-4 | |
| PROPANOL, (2-METHOXYMETHYLETH-OXY)- | 34590-94-8 | |

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

| Proposition 65 List of chemicals | | | | | |
|----------------------------------|------------------------|-----------|-----|--|----------------------|
| Name of substance | Name acc. to inventory | CAS No | Wt% | Remarks | Type of the toxicity |
| C.I. Pigment Black 7 | carbon black | 1333-86-4 | 11 | airborne, unbound particles of respirable size | cancer |

VOC content

- Regulated Volatile Organic Compounds (VOC-EPA) 7.5 %
- Regulated Volatile Organic Compounds (VOC-Cal ARB) 28 %

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

| Category | Rating | Description |
|---------------------|--------|--|
| Chronic | * | chronic (long-term) health effects may result from repeated overexposure |
| Health | 0 | no significant risk to health |
| Flammability | 2 | material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur |
| Physical hazard | 0 | material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive |
| Personal protection | - | |

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Cook Auto Supply Black Trim Kote

Version number: GHS 1.0

Date of compilation: 2021-10-11

| Category | Degree of hazard | Description |
|----------------|------------------|--|
| Flammability | 2 | material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur |
| Health | 1 | material that, under emergency conditions, can cause significant irritation |
| Instability | 0 | material that is normally stable, even under fire conditions |
| Special hazard | | |

National inventories

| Country | Inventory | Status |
|---------|------------|--------------------------------|
| CA | DSL | not all ingredients are listed |
| EU | REACH Reg. | not all ingredients are listed |
| US | TSCA | not all ingredients are listed |

Legend

DSL Domestic Substances List (DSL)
REACH Reg. REACH registered substances
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

| Abbr. | Descriptions of used abbreviations |
|------------------|--|
| 29 CFR 1910.1000 | 29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits) |
| 49 CFR US DOT | 49 CFR U.S. Department of Transportation |
| ACGIH® 2019 | From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement |
| Cal/OSHA PEL | California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs) |
| Cal ARB | California Air Resources Board |
| Carc. | Carcinogenicity |
| CAS | Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances) |
| Ceiling-C | Ceiling value |
| DGR | Dangerous Goods Regulations (see IATA/DGR) |
| DNEL | Derived No-Effect Level |
| DOT | Department of Transportation (USA) |
| EC50 | Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval |
| EmS | Emergency Schedule |
| EPA | Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment |
| ErC50 | ≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control |

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Cook Auto Supply Black Trim Kote

Version number: GHS 1.0

Date of compilation: 2021-10-11

| Abbr. | Descriptions of used abbreviations |
|----------------|---|
| ERG No | Emergency Response Guidebook - Number |
| Flam. Liq. | Flammable liquid |
| GHS | "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations |
| IARC | International Agency for Research on Cancer |
| IATA | International Air Transport Association |
| IATA/DGR | Dangerous Goods Regulations (DGR) for the air transport (IATA) |
| ICAO | International Civil Aviation Organization |
| ICAO-TI | Technical instructions for the safe transport of dangerous goods by air |
| IMDG | International Maritime Dangerous Goods Code |
| IMDG-Code | International Maritime Dangerous Goods Code |
| LC50 | Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval |
| MARPOL | International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant") |
| NIOSH REL | National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs) |
| NPCA-HMIS® III | National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition |
| OSHA | Occupational Safety and Health Administration (United States) |
| PBT | Persistent, Bioaccumulative and Toxic |
| PEL | Permissible exposure limit |
| PNEC | Predicted No-Effect Concentration |
| ppm | Parts per million |
| RTECS | Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information) |
| STEL | Short-term exposure limit |
| TLV® | Threshold Limit Values |
| TWA | Time-weighted average |
| VOC | Volatile Organic Compounds |
| vPvB | Very Persistent and very Bioaccumulative |

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

| Code | Text |
|------|---------------------|
| H227 | Combustible liquid. |
| H350 | May cause cancer. |

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Cook Auto Supply Black Trim Kote

Version number: GHS 1.0

Date of compilation: 2021-10-11

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.