SECTION 1 - IDENTIFICATION

MANUF / DIST: COOK AUTO SUPPLY

3590 NORTH 126th STREET

BROOKFIELD, WI 53005

PREPARER / CONTACT: TOM COOK PREPARER PHONE: 262-783-1539

24 HOUR EMERGENCY PHONE: INFOTRAC 1-800-535-5053

ULTIMATE RAIN SHINE TRADE NAME / SYNONYMS:


NOT APPLICABLE CHEMICAL NAME / SYNONYMS: CHEMICAL FAMILY: NOT APPLICABLE FORMULA: **PROPRIETARY** PRODUCT CODE: NOT APPLICABLE

SECTION 2. HAZARDOUS IDENTIFICATION

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM:

HAZARD WARNING

- 4 Extreme
- 3 High
- 2 Moderate
- 1 Slight
- 0 Insignificant
- X- See Section IV & V of SDS Sheet





Signal Word: WARNING! - FOR HEALTH EFFECTS (Acute and Chronic): SEE SECTION 11

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

NAMES OF HAZARDOUS INGREDIENTS: See CFR29§1910.1200 (i)-(13) [exact % withheld as trade secret] CHEMICAL / COMMON NAME CAS# PERCENTAGE PEL-OSHA **TLV-ACGIH**

No components listed in Haz Met Materials, no DOT number necessary

SECTION 4 - FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURES:

- a) Skin Immediately flush skin with lots of running water for at least 30 minutes. Remove contaminated clothing and shoes. Wash before reuse.
- b) Eyes Flush immediately with large quantities of running water for at least 15 minutes. Consult Physician.
- c) Inhalation If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet and get medical attention.
- d) Ingestion Do not induce vomiting. Call physician immediately. If conscious give lots of water or milk. Do not give anything by mouth to an unconscious or convulsing person.

SECTION 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA:

Product is not a fire hazard, but it's residue can burn, after water evaporates. In case of fire use water spray, carbon dioxide, alcohol type foam applied by manufactures recommended techniques. *See additional comments Keep containers cool with water spray using fog nozzles.

HAZARDOUS DECOMPOSITION PRODUCTS: After water evaporates, residue may burn to give oxides of carbon and traces of hydrocarbons.

SPECIAL FIRE FIGHTING PROCEDURES: None UNUSUAL FIRE AND EXPLOSION HAZARDS: None

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Avoid contact with alkalis, glass, concrete and other silicone containing materials, metals and many other materials including rubber, leather, and certain organic substances.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

- a) Do not store under freezing conditions or above 120 degrees F.
- b) Do not store near acids or acidic materials and oxidizers.

MAINTENANCE PRECAUTIONS:

When working with FLAMMABLE material electrically ground all

equipment and use only non-sparking tools.

INCOMPATIBILITY (Material To Avoid): Salt solutions or acids may coagulate the product.

OTHER PRECAUTIONS:

Containers, even those that have been emptied will retain product residue and vapors. Always obey hazard warnings.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION:

LOCAL EXHAUST: Below TLV(s)MECHANICAL (General): Explosion Proof

SPECIAL: N/A OTHER: N/A RESPIRATORY

PROTECTION: An appropriate NIOSH hydrocarbon canister or respirator for organic vapor should be worn if needed.

PROTECTIVE GLOVES:

Wear - resistant gloves such as nitrile rubber, PVC, etc.

OTHER PROTECTIVE EQUIPMENT:

Eye wash and quick drench facilities. OTHER ENGINEERING CONTROLS: None Known

WORK PRACTICES:

Eye wash fountain and safety shower should be accessible. Discard properly such items as rags and trash soaked with the product. Provide adequate

ventilation.

HYGIENIC PRACTICES:

Avoid contact with eyes, skin and clothing. Avoid inhalation of product vapors. Wash thoroughly after handling and before eating, drinking or smoking. Remove contaminated clothing promptly and wash thoroughly before reused.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (F):	>212	SPECIFIC GRAVITY (WATER=1):	1.00
VAPOR PRESSURE (mmHg):	N/E	PERCENT VOLATILE BY VOLUME (%):	78.00
VAPOR DENSITY (AIR=1):	N/E	EVAPORATION RATE (WATER=1)	<1
FLASH POINT (Method Used):	None	FLAMMABLE LIMITS: LEL= N/A UEL=N/A	

SOLUBILITY IN WATER: 100% APPEARANCE,ODOR,VISCOSITY:: Tan leather odor milky liquid.

pH N/A Melting pt-N/A /freezing pt 30+-°F/Relative density N/A

SECTION 10 - STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION WILL NOT OCCUR

THIS PRODUCT IS STABLE

SECTION 11 - TOXICOLOGICAL INFORMATION

FOR NUMERICAL MEASURES OF TOXICITY SEE SECTION 3, COLUMNS (PEL-OSHA)AND(TLV-ACGIH) HEALTH EFFECTS (Acute and Chronic):

Acute:

- a) Eyes Can cause severe irritation, redness, tearing, blurred vision.
- b) Skin Prolonged or repeated contact can cause moderate irritation defatting, dermatitis.
- c) Inhalation Mild irritation.
- d) Ingestion Can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic

a) Inhalation may increase susceptibility to respiratory illness.

PRIMARY ROUTES OF ENTRY:

a) Skin b) Inhalation

THIS PRODUCT DOES NOT CONTAIN CARCINOGENS: (NTP, IARC, OSHA)

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Pre-existing skin, eye and respiratory disorders may be aggravated by exposure to product.

SECTION 12 - ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: N/A 100% BIODEGRADABLE ECOTOXICOLOGICAL INFORMATION: N/A

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS:

Dispose of according to local, state and federal regulations for products containing organic polymers.

SECTION 14 - TRANSPORT INFORMATION

SHIPPING INFO, UN/NA #'s, Secondary container label INFO NECESSARY OR SUGGESTED:

CONTAINS NO HAZ MET - NO DOT NUMBER NECESSARY KEEP OUT OF THE REACH OF CHILDREN!

SECTION 15 - REGULATORY INFORMATION

THIS PRODUCT DOES NOT CONTAIN CARCINOGENS: (NTP, IARC, OSHA)

SECTION 16 - OTHER INFORMATION

KEEP OUT OF THE REACH OF CHILDREN!

IN CLOSE COOPERATION OF THE US GOVERNMENT'S PAPER REDUCTION ACT, AND ALSO IN EFFORT TO PROVIDE FULL AND COMPLETE INFORMATION AS SUGGESTED BY THE OSHA GUIDELINES, AND KEEPING IN ALIGNMENT WITH THE SOCIETY for CHEMICAL HAZARD COMMUNICATION (SCHC) AND WE HAVE BEEN ABLE TO KEEP ALL IN 4 PAGES..

THESE SDS SHEETS ARE WRITTEN IN AN EFFORT TO PROVIDE INFORMATION TO THE WORKER IN THE WORKPLACE AND IN SUCH A WAY IT CAN BE UNDERSTOOD.

We have enjoyed many compliments as to the readability and understandable content, and take great pride in providing these Safety Data Sheets to the use of our customers.

The International Labour Organization has suggested 16 sections of the sheets, and we have re adjusted the 8 part, and rearranged the information, and renamed the sheets from MATERIAL Safety Data Sheets to SAFETY DATA SHEETS. THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE. IT IS PROVIDED FOR A CONTINUING SAFETY PROGRAM INITIATED BY THE MANUFACTURER/DISTRIBUTOR NAMED ON THIS SHEET. IT IS NOT INTENDED TO CONSTITUTE PERFORMANCE INFORMATION CONCERNING THE PRODUCT. NO EXPRESS WARRANTY, OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IS MADE WITH RESPECT TO THE PRODUCT OR THE INFORMATION CONTAINED HEREIN.

Please note that several items were left out of section 9 because they do not affect the worker in the workplace. Partition coefficient: n-octanol/water; • Auto-ignition temperature; • Decomposition temperature and Odor threshold.