MATERIAL SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: USED CAR GLAZE DISTRIBUTOR Cook Auto Supply

SYNONYMS: NA ADDRESS: 3590 N. 126th Street

PRODUCT CODES: UCG 408 Brookfield WI 53005 USA

PRODUCT USE: Vehicle Compound PHONE NUMBER: 262-783-1539
PREPARED BY: Robert Blahnik FAX NUMBER: 262-783-1547

DATE PREPARED: 17-Feb-2014 24 HOUR EMERGENCY USA/CANADA: INFOTRAC 1-800-535-5053

DATE REVISED: NA 24 HOUR EMERGENCY INTERNATIONAL: INFOTRAC 1-352-323-3500

SECTION 2: HAZARDOUS INGREDIENTS

Components not listed are either non-hazardous or in concentrations of less than 1%

HAZARDOUS INGREDIENT:CAS NO:% WT:Mineral Spirits Aliphatics64742-48-920-25%

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: May be harmful if swallowed

ROUTE(S) OF ENTRY: INHALATION: Yes SKIN: Yes INGESTION: Yes EYES: Yes

POTENTIAL HEALTH EFFECTS INHALATION: Vapors - Irritant SKIN: Irritant INGESTION: Harmful EYES: Irritant

ACUTE HEALTH HAZARDS: Prolonged skin contact may cause slight irritation. Ingestion can cause gastrointestinal irritation.

Can cause eye irritation. Excessive inhalation may cause respiratory irritation.

CHRONIC HEALTH HAZARDS: Irritation, headache, nausea, vomiting, central nervous system depression.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: May aggravate pre-existing skin conditions.

CARCINOGENICITY OSHA: Not Listed ACGIH: Not Listed NTP: Not listed IARC: Not Listed OTHER:

SECTION 4: FIRST AID MEASURES

EYES: Flush with water, especially under eyelids, for at least 15 minutes. Call physician.

SKIN: Wash with soap and water, see physician if irritation persists.

INHALATION: Remove to fresh air, give oxygen if needed.

INGESTION: Do not induce vomiting. Get medical attention immediately.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS: None beyond listed above

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR (% BY VOLUME) UPPER: LOWER:

FLASH POINT: >200 F >93.3 C METHOD USED: TCC AUTOIGNITION TEMPERATURE: F

NFPA HAZARD CLASSIFICATION: TOXICITY: 1 FLAMMABILITY: 1 REACTIVITY: 0 OTHER:

HMIS HAZARD CLASSIFICATION: HEALTH: 1 FLAMMABILITY: 1 REACTIVITY: 0 PROTECTION:

EXTINGUISHING MEDIA: Foam, carbon dioxide, dry chemical

SPECIAL FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water.

UNUSUAL FIRE AND EXPLOSION HAZARDS: See hazardous decompositions

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon monoxide and other inidentified organic compounds may be released during combustion.

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: Contain spill. Remove with inert absorbent material. Wash spill area with water.

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE:

Store containers upright with lids (caps) tightly closed. Store between 40F(4C) - 100F(37.7C) Keep from freezing.

OTHER PRECAUTIONS: Keep out of the reach of children. Do not get in eyes or on skin.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS: <u>CAS NO.</u> <u>OSHA PEL-TWA:</u> <u>OSHA PEL STEL:</u> <u>ACGIH TLV-TWA:</u>

Mineral Spirits Aliphatics 64742-48-9 100ppm 200 ppm 500ppm

VENTILATION: LOCAL EXHAUST: Adequate MECHANICAL: OTHER:

RESPIRATORY PROTECTION: Avoid exposure levels. When exceeded, use self contained breathing apparatus.

EYE PROTECTION: Approved Safety Glasses SKIN PROTECTION: Rubber or Neoprene Gloves

PROTECTIVE CLOTHING OR EQUIPMENT: Eye wash fountain in work area is recommended.

WORK HYGIENIC PRACTICES: Observe good housekeeping practices.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Pale Green odor: Solvent pH AS SUPPLIED: pH (Other):

PHYSICAL STATE: Viscous Cream 90%

BOILING POINT: 220 F 104 C VAPOR PRESSURE (mmHg):

MELTING POINT: F C VAPOR DENSITY (AIR = 1): >1 FREEZING POINT: F C SPECIFIC GRAVITY (H2O = 1): 1 < 1

EVAPORATION RATE: BASIS (Butyl Acetate=1): 1 VISCOSITY:

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable conditions to avoid: Open flame

INCOMPATIBILITY (MATERIAL TO AVOID): Strong acids or bases, oxidizing agents.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

Carbon monoxide and other inidentified organic compounds may be released during combustion.

HAZARDOUS POLYMERIZATION: Will not occur CONDITIONS TO AVOID (POLYMERIZATION): NA

SECTION 11: TOXICOLOGICAL INFORMATION

HAZARDOUS INGREDIENT(S) CAS NO. LD50 ORAL/RAT

Mineral Spirits Aliphatics 64742-48-9 LD50 > 18.8 g/kg Kidney damage in male rats.

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: ND MARINE POLLUTANT: ND

SECTION 13: DISPOSAL CONSIDERATIONS

waste disposal method: In accordance with Federal, State and local regulations.

RCRA HAZARD CLASS: Not Regulated

SECTION 14: TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION (DOT)

PROPER SHIPPING NAME: Cleaning Compounds Not regulated in accordance with the 49 CFR

IATA - AIR TRANSPORTATION

PROPER SHIPPING NAME: Cleaning Compounds Not regulated in accordance with IATA

IMDG - WATER TRANSPORTATION

PROPER SHIPPING NAME: Cleaning Compounds Not regulated in accordance with IMDG

OTHER AGENCIES: NA

Cook Auto Supply Page 2 of 3 Used Car Glaze UCG408

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA (TOXIC SUBSTANCE CONTROL ACT): All chemical substances in this material are included on or exempted from listing (

the TSCA Inventory of Chemical Substances

EPA SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT):

302 EXTREMELY HAZARDOUS SUBSTANCES: None

304 CERCLA HAZARDOUS SUBSTANCES: None

311/312 HAZARD CLASS: <u>CAS NO.</u> <u>HAZARD CLASS:</u>

Mineral Spirits Aliphatics 64742-48-9 Chronic, Fire

313 TOXIC CHEMICALS: None

U.S. STATE REGULATIONS: Not regulated in any state

WHMIS (CANADA) HAZARD SYMBOL AND CLASSIFICATION Not regulated

INTERNATIONAL REGULATIONS: DSCL (EEC): This product is not classified according to the EU regulations.

INTERNATIONAL LISTS:

All chemical substances in this material are included on or exempted from listing on the following lists: Australia (AICS),

Canada (DSL/NDSL), Europe (EINECS/ELINCS), Korea (TCCL), Japan (METI), the Philippines (RA6969).

SECTION 16: OTHER INFORMATION

PREPARATION INFORMATION: Cook Auto Supply

• END OF DOCUMENT •